

insight
unleashed



 **quickview**[®]
airHD

an instant,
wireless view
into any sewer



Envirosight

sewer assessment

that unleashes
your insight

A complete sewer assessment is essential to prioritizing CCTV and maintenance activities, planning cleaning and rehab work, and meeting regulatory obligations.

Quickview airHD makes it easier, faster and more affordable to assess sewer condition, offering productivity features like:

- | | | |
|----------------|----------------------|----------------------|
| HD video | wireless operation | touchscreen controls |
| motorized tilt | hands-free stability | remote centering |



Quad Haloptic. Our patented Haloptic technology gives you more illumination farther into the pipe with optimum alignment at every distance. The new Quad Haloptic configuration uses four offset reflector/lamp pairs to fully encircle the camera with powerful light.

HALOPTIC

Smart Center. To adjust camera height in-manhole, push against the standoff's gas spring to the desired height; a ratchet then holds your position.

Wi-Fi. Wireless control and video eliminates cables and allows live video sharing on multiple devices.

Connection. Connect to any Quickview airHD in range, either in control or view-only mode. Download app updates to access new features.

Status Bar. Monitor illumination, zoom and tilt, as well as Wi-Fi signal and battery (for both tablet and camera).

Capture. Record video and capture still images to the media library.

HD Zoom

Tilt

Illumination

Media Library. Browse media thumbnails, then review, annotate and share footage.

Text Overlay. Configure on-screen display of text, including variables like zoom, tilt and GPS coordinates. Modify text color and position.



- camera head
- pole
- standoff
- bipod
- battery (2)
- battery charger
- case
- app (*tablet device not included*)



www.envirosight.com

(866) 936-8476 • (973) 252-6700

111 Canfield Ave., Unit B3
Randolph, NJ 07869

video system

imager	1/2.8-type CMOS
zoom	360× (30× optical, 12× digital)
resolution	1280×720 pixels (2.38 megapixels)
functions	zoom
	focus (auto/manual)
	shutter (auto/manual)
	sensitivity mode
field of view (hor.)	63.7 deg (wide) - 2.3 deg (tele)
sensitivity	1.4 lux

system	Quad Haloptic (four LED/reflector pairs)
illumination type	coaxial, collimated
reflector type	proprietary

connections	4-pin auxiliary port
depth rating	10' (3m)
construction	aluminum, rubber, acrylic
sensors	temperature, pressure, incline

Wi-Fi standard	IEEE 802.11b/g/n
frequency range	2.400–2.483 GHz
operating channels	1–11

extension range 18.9" (480mm)
pipe diameter compatibility . . . 6-48" (DIN 150-1200)
mechanism . . . gas spring with reciprocating ratchet

battery quantity	2
battery capacity	3.4 A-hr.
battery charger	mains power

length (collapsed/extended) 4'/16' (nominal)
stabilization detachable hands-free support

supported OS Android, iOS, Windows