


**Prepared For:**  
 VILLAGE OF ORLAND PARK  
 TOM MORGAN  
 15655 S Ravinia Ave.  
 Orland Park, IL 60462-4634  
 (708)403 - 6350  
 Reference ID: N9 SCR

**Presented By:**  
 RUSH TRK CTR OF N IL  
 William Hildreth  
 11816 S IL RTE 47  
 HUNTLEY IL 60142  
 847-669-5700

Thank you for the opportunity to provide you with the following quotation on a new International truck. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

**2017 MODEL YEAR CAB AND CHASSIS ONLY**  
**THIS SPECIFICATION WILL ACCEPT THE INSTALLATION OF THE FOLLOWING**  
**SNOW REMOVAL EQUIPMENT:**  
**10 FT DUMP WITH WET SYSTEM TANK BEHIND CAB**  
**FRONT PLOW**  
**TAILGATE SALT SPREADER**



**Model Profile**  
**2017 7400 SBA 4X2 (SA625)**

**APPLICATION:** Construction Dump  
**MISSION:** Requested GVWR: 37780. Calc. GVWR: 37780  
 Calc. Start / Grade Ability: 31.86% / 3.06% @ 55 MPH  
 Calc. Geared Speed: 68.6 MPH  
**DIMENSION:** Wheelbase: 169.00, CA: 101.90, Axle to Frame: 63.00  
**ENGINE, DIESEL:** {Navistar N9} EPA 2010, SCR, 315 HP @ 2000 RPM, 950 lb-ft Torque @ 1200 RPM, 2200 RPM Governed Speed, 315 Peak HP (Max)  
**TRANSMISSION, AUTOMATIC:** {Allison 3000\_RDS\_P} 5th Generation Controls; Close Ratio, 6-Speed, With Double Overdrive; On/Off Hwy; Includes Oil Level Sensor, With PTO Provision, Less Retarder, With 80,000-lb GVW & GCW Max.  
**CLUTCH:** Omit Item (Clutch & Control)  
**AXLE, FRONT NON-DRIVING:** {Meritor MFS-16-143A} Wide Track, I-Beam Type, 16,000-lb Capacity  
**AXLE, REAR, SINGLE:** {Dana Spicer S26-190} Single Reduction, 26,000-lb Capacity, R Wheel Ends Gear Ratio: 6.14  
**CAB:** Conventional  
**TIRE, FRONT:** (3) 12R22.5 G661 HSA (GOODYEAR) 484 rev/mile, load range H, 16 ply  
**TIRE, REAR:** (4) 12R22.5 G622 RSD (GOODYEAR) 482 rev/mile, load range H, 16 ply  
**SUSPENSION, RR, SPRING, SINGLE:** Vari-Rate; 31,000-lb Capacity, Includes 4500-lb Capacity Multileaf Auxiliary  
**PAINT:** Cab schematic 100GN  
 Location 1: 2303, Red (Std)  
 Chassis schematic N/A

<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
<b>Base Chassis, Model 7400 SBA 4X2 with 169.00 Wheelbase, 101.90 CA, and 63.00 Axle to Frame.</b>	7125/3517	10642
FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.866" x 3.622" x 0.433" (276.0mm x 92.0mm x 11.1mm); 456.0" (11582mm) Maximum OAL	163/356	519
BUMPER, FRONT Steel, Swept Back; Painted 0001 Canyon Black	0/0	0
FRAME EXTENSION, FRONT Integral; 20" In Front of Grille	140/-35	105
WHEELBASE RANGE 138" (350cm) Through and Including 187" (475cm)	0/0	0
AXLE, FRONT NON-DRIVING {Meritor MFS-16-143A} Wide Track, I-Beam Type, 16,000-lb Capacity	95/0	95
<u>Notes</u> : The following features should be considered when calculating Front GAWR: Front Axles; Front Suspension; Brake System; Brakes, Front Air Cam; Wheels; Tires.		
SHOCK ABSORBERS, FRONT	47/0	47
SPRINGS, FRONT AUXILIARY Rubber	10/0	10
SUSPENSION, FRONT, SPRING Multileaf, Shackle Type; 16,000-lb Capacity; Less Shock Absorbers	235/1	236
<u>Includes</u> : SPRING PINS Rubber Bushings, Maintenance-Free		
<u>Notes</u> : The following features should be considered when calculating Front GAWR: Front Axles; Front Suspension; Brake System; Brakes, Front Air Cam; Wheels; Tires.		
BRAKE SYSTEM, AIR Dual System for Straight Truck Applications	0/0	0
<u>Includes</u> : BRAKE LINES Color and Size Coded Nylon : DRAIN VALVE Twist-Type : GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster : PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel : PARKING BRAKE VALVE For Truck : QUICK RELEASE VALVE Bendix On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4 : SLACK ADJUSTERS, FRONT Automatic : SLACK ADJUSTERS, REAR Automatic : SPRING BRAKE MODULATOR VALVE R-7 for 4x2, SR-7 with relay valve for 6x4		
<u>Notes</u> : Rear Axle is Limited to 23,000-lb GAWR with Code 04091 BRAKE SYSTEM, AIR and Standard Rear Air Cam Brakes Regardless of Axle/Suspension Ordered.		
BRAKES, FRONT, AIR CAM 16.5" x 6", Includes 24 Sqn Long Stroke Brake Chambers	0/0	0
<u>Notes</u> : The following features should be considered when calculating Front GAWR: Front Axles; Front Suspension; Brake System; Brakes, Front Air Cam; Wheels; Tires.		
TRAILER CONNECTIONS Four-Wheel, With Hand Control Valve and Tractor Protection Valve, for Straight Truck	2/0	2
AIR BRAKE ABS {Bendix AntiLock Brake System} Full Vehicle Wheel Control System (4-Channel) With Automatic Traction Control	0/0	0
AIR DRYER {Bendix AD-IP} With Heater	21/4	25
<u>Includes</u> : AIR DRYER LOCATION Inside Left Rail, Back of Cab		

<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 Spring Brake	0/0	0
BRAKE CHAMBERS, FRONT AXLE {Bendix} 24 SqIn	0/0	0
SLACK ADJUSTERS, FRONT {Haldex} Automatic	6/0	6
SLACK ADJUSTERS, REAR {Haldex} Automatic	0/0	0
BRAKES, REAR, AIR CAM S-Cam; 16.5" x 7.0"; Includes 30/30 Sq.In. Long Stroke Brake Chamber and Spring Actuated Parking Brake	0/0	0
<u>Notes</u>		
: The following features should be considered when calculating Rear GAWR: Rear Axles; Rear Suspension; Brake System; Brakes, Rear Air Cam; Brake Shoes, Rear; Special Rating, GAWR; Wheels; Tires.		
AIR COMPRESSOR {Bendix Tu-Flo 550} 13.2 CFM Capacity	0/0	0
DRAIN VALVE (3) Petcocks; for Air Tanks	0/0	0
STEERING COLUMN Tilting	0/0	0
STEERING WHEEL 2-Spoke, 18" Dia., Black	0/0	0
STEERING GEAR {Sheppard M110} Power	0/0	0
EXHAUST SYSTEM Switchback Horizontal Aftertreatment Device, Frame Mounted Right Side Under Cab; Includes Single Vertical Tail Pipe, Frame Mounted Right Side Back of Cab	122/-19	103
TAIL PIPE (1) Turnback Type, Bright, for Single Exhaust	0/0	0
MUFFLER/TAIL PIPE GUARD (1) Bright Stainless Steel	0/0	0
ELECTRICAL SYSTEM 12-Volt, Standard Equipment	0/0	0
<u>Includes</u>		
: DATA LINK CONNECTOR For Vehicle Programming and Diagnostics In Cab		
: FUSES, ELECTRICAL SAE Blade-Type		
: HAZARD SWITCH Push On/Push Off, Located on Top of Steering Column Cover		
: HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever		
: HEADLIGHTS (2) Sealed Beam, Round, with Chrome Plated Bezels		
: JUMP START STUD Located on Positive Terminal of Outermost Battery		
: PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light		
: STARTER SWITCH Electric, Key Operated		
: STOP, TURN, TAIL & B/U LIGHTS Dual, Rear, Combination with Reflector		
: TURN SIGNAL SWITCH Self-Cancelling for Trucks, Manual Cancelling for Tractors, with Lane Change Feature		
: WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever		
: WINDSHIELD WIPERS Single Motor, Electric, Cowl Mounted		
: WIRING, CHASSIS Color Coded and Continuously Numbered		
POWER SOURCE Cigar Type Receptacle without Plug and Cord	1/0	1
ALTERNATOR {Leece-Neville AV1160P2013} Brush Type; 12 Volt 160 Amp. Capacity, Pad Mount, With Remote Sense	0/0	0
<b>BODY BUILDER WIRING INSIDE CAB; Includes Sealed Connectors for Tail/Amber, Turn/Marker/Backup/Accessory, Power/Ground, and Stop/Turn</b>	0/0	0
BATTERY SYSTEM {International} Maintenance-Free (3) 12-Volt 2775CCA Total	49/14	63
2-WAY RADIO Wiring Effects; Wiring With 20 Amp Fuse Protection, Includes Ignition Wire With 5 Amp Fuse, Wire Ends Heat Shrink and Routed to Center of Header Console in Cab	1/0	1

<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
RADIO {Panasonic CQ120} AM/FM, Includes Multiple Speakers, Includes Auxiliary Input	2/0	2
<u>Includes</u>		
: SPEAKERS IN CAB (2) Dual-Cone with Deluxe Interior		
: SPEAKERS IN CAB (4) Coaxial with Premium Interior		
AUXILIARY HARNESS 3.0' for Auxiliary Front Head Lights and Turn Signals for Front Plow Applications	2/0	2
TRAILER CONNECTION SOCKET 7-Way; Mounted at Rear of Frame, Wired for Turn Signals Combined With Stop, Compatible With Trailers That Use Combined Stop, Tail, Turn Lamps	0/7	7
<b>BATTERY CABLES With 36" of Extra Length Coiled and Strapped Near Battery Box</b>	0/0	0
HORN, ELECTRIC Disc Style	0/0	0
BATTERY BOX Steel With Plastic Cover, 18" Wide, 2, 3, or 4 Battery Capacity, Mounted Right Side Back of Cab	-28/8	-20
<b>SWITCH, BODY CIRCUITS, MID for Bodybuilder, 6 Momentary Switches in Instrument Panel; One Power Module with 6 Channels, 20 Amp Max. Per Channel, 80 Amp Max Output, Switches Control Power Module Through Multiplex Wiring, Mounted in Cab Behind Driver Seat</b>	1/0	1
HORN, AIR Black, Single Trumpet, Air Solenoid Operated	0/0	0
WINDSHIELD WIPER SPD CONTROL Force Wipers to Slowest Intermittent Speed When Park Brake Set and Wipers Left on for a Predetermined Time	0/0	0
SWITCH, TOGGLE, FOR WORK LIGHT Lighted; on Instrument Panel and Wiring Effects for Customer Furnished Back of Cab Light	2/1	3
CLEARANCE/MARKER LIGHTS (5) {Truck Lite} Amber LED Lights, Flush Mounted on Cab or Sunshade	0/0	0
ENGINE SHUTDOWN Automatic; With 30 Second Delay, With International Engines	1/0	1
TEST EXTERIOR LIGHTS Pre-Trip Inspection will Cycle all Exterior Lamps Except Back-up Lights	0/0	0
HEADLIGHTS ON W/WIPERS Headlights Will Automatically Turn on if Windshield Wipers are turned on	0/0	0
STARTING MOTOR {Delco Remy 38MT Type 300} 12 Volt; less Thermal Over-Crank Protection	0/0	0
INDICATOR, LOW COOLANT LEVEL With Audible Alarm	0/0	0
ALARM, PARKING BRAKE Electric Horn Sounds in Repetitive Manner When Vehicle Park Brake is "NOT" Set, With Ignition "OFF" and any Door Opened	0/0	0
TURN SIGNALS, FRONT LED, Includes LED Side Marker Lights, Mounted on Fender	0/0	0
INSULATION, UNDER HOOD for Sound Abatement	10/0	10
GRILLE Stationary, Chrome	0/0	0
INSULATION, SPLASH PANELS for Sound Abatement	2/0	2
FRONT END Tilting, Fiberglass, With Three Piece Construction; for 2007 & 2010 Emissions	0/0	0
PAINT SCHEMATIC, PT-1 Single Color, Design 100	0/0	0
<u>Includes</u>		
: PAINT SCHEMATIC ID LETTERS "GN"		
PAINT TYPE Base Coat/Clear Coat, 1-2 Tone	0/0	0
VEHICLE REGISTRATION IDENTITY ID for 49 States, Excluding California	0/0	0

<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
PROMOTIONAL PACKAGE Government and Municipal Silver Package; Two Year Limited Subscription of On-Command Service Information (Formerly Fleet ISIS), and On-Command Parts Information (Formerly Fleet Parts Catalog), Requires Specific Feature Combinations	0/0	0
CLUTCH Omit Item (Clutch & Control)	-63/-12	-75
ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection	0/0	0
ENGINE, DIESEL {Navistar N9} EPA 2010, SCR, 315 HP @ 2000 RPM, 950 lb-ft Torque @ 1200 RPM, 2200 RPM Governed Speed, 315 Peak HP (Max)	0/0	0
<u>Includes</u>		
: AIR COMPRESSOR AIR SUPPLY LINE Naturally-Aspirated (Air Brake Chassis Only)		
: COLD STARTING EQUIPMENT Intake Manifold Electric Grid Heater with Engine ECM Control		
: CRUISE CONTROL Electronic; Controls Integral to Steering Wheel		
: ENGINE OIL DRAIN PLUG Magnetic		
: ENGINE SHUTDOWN Electric, Key Operated		
: FUEL FILTER Included with Fuel/Water Separator		
: FUEL/WATER SEPARATOR Fuel/Water Separator and Fuel Filter in a Single Assembly; With Water-in-Fuel Sensor; Engine Mounted		
: GOVERNOR Electronic		
: OIL FILTER, ENGINE Spin-On Type		
: WET TYPE CYLINDER SLEEVES		
FAN DRIVE {Horton Drivemaster Polar Extreme} Direct Drive Type, Two Speed, With Residual Torque Device for Disengaged Fan Speed	0/0	0
<u>Includes</u>		
: FAN Nylon		
RADIATOR Aluminum, Cross Flow, Series System; 1228 SqIn Core and 648 SqIn Charge Air Cooler and With Transmission Oil Cooler	0/0	0
FEDERAL EMISSIONS {Navistar N9 & N10} EPA, OBD and GHG Certified for Calendar Year 2016	0/0	0
AIR CLEANER Single Element, with Integral Snow Valve and In-Cab Control	2/0	2
<u>Includes</u>		
: GAUGE, AIR CLEANER RESTRICTION Air Cleaner Mounted		
THROTTLE, HAND CONTROL Engine Speed Control; Electronic, Stationary, Variable Speed; Mounted on Steering Wheel	0/0	0
ENGINE CONTROL, REMOTE MOUNTED Provision for; Includes Wiring for Body Builder Installation of PTO Controls; With Ignition Switch Control for MaxxFORCE and Navistar post 2007 Emissions Electronic Engines	0/0	0
BLOCK HEATER, ENGINE {Phillips} 120V/1250W, With "Y" Cord From Socket in Standard Location, For a Dealer Installed Oil Pan Heater, With Extended Life Coated Metal/Plastic/Metal Material Oil Pan	4/0	4
<u>Includes</u>		
: BLOCK HEATER SOCKET Receptacle Type; Mounted below Drivers Door		
<u>Notes</u>		
: MPM material is single sheet composite with two layers of sheet metal sandwiching plastic material. MPM material has electro-deposition prime coat with powder coating for the final finish coat.		
EMISSION COMPLIANCE Federal, Does Not Comply With California Clean Air Idle Regulations	0/0	0
TRANSMISSION, AUTOMATIC {Allison 3000_RDS_P} 5th Generation Controls; Close Ratio, 6-Speed, With Double Overdrive; On/Off Hwy; Includes Oil Level Sensor, With PTO Provision, Less Retarder, With 80,000-lb GVW & GCW Max.	195/54	249
TRANSMISSION SHIFT CONTROL {Allison} Push-Button Type; for Allison 3000 & 4000 Series Transmission	0/0	0

<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
TRANSMISSION DIPSTICK Relocated to Right Side of Transmission	0/0	0
TRANSMISSION OIL Synthetic; 29 thru 42 Pints	0/0	0
ALLISON SPARE INPUT/OUTPUT for Rugged Duty Series (RDS); General Purpose Trucks, Construction	0/0	0
<b>TRANSMISSION TCM LOCATION Located Inside Cab</b>	0/0	0
SHIFT CONTROL PARAMETERS Allison 3000 or 4000 Series Transmissions, 5th Generation Controls, Performance Programming	0/0	0
PTO CONTROL, DASH MOUNTED For Customer Provided PTO; Includes Switch, Electric/Air Solenoid, Piping and Wiring	3/0	3
PTO LOCATION Left Side of Transmission	0/0	0
AXLE, REAR, SINGLE {Dana Spicer S26-190} Single Reduction, 26,000-lb Capacity, R Wheel Ends . Gear Ratio: 6.14	0/369	369
<u>Includes</u>		
: REAR AXLE DRAIN PLUG (1) Magnetic, For Single Rear Axle		
<u>Notes</u>		
: The following features should be considered when calculating Rear GAWR: Rear Axles; Rear Suspension; Brake System; Brakes, Rear Air Cam; Brake Shoes, Rear; Special Rating, GAWR; Wheels; Tires.		
: When Specifying Axle Ratio, Check Performance Guidelines and TCAPE for Startability and Performance		
SUSPENSION, RR, SPRING, SINGLE Vari-Rate; 31,000-lb Capacity, Includes 4500-lb Capacity Multileaf Auxiliary	0/88	88
<u>Notes</u>		
: The following features should be considered when calculating Rear GAWR: Rear Axles; Rear Suspension; Brake System; Brakes, Rear Air Cam; Brake Shoes, Rear; Special Rating, GAWR; Wheels; Tires.		
AXLE, REAR, LUBE {EmGard FE-75W-90} Synthetic Oil; 30 thru 39.99 Pints	0/0	0
FUEL TANK STRAPS Bright Finish Stainless Steel	0/0	0
FUEL/WATER SEPARATOR with Thermostatic Fuel Temperature Controlled Electric Heater, and Filter Restriction/Change Indicator, Includes Standard Equipment Water-in-Fuel Sensor	5/0	5
FUEL TANK Top Draw; D-Style, Non-Polished Aluminum, 19" Deep, 50 U.S. Gal., 189 L Capacity, with Quick Connect Outlet, Mounted Left Side, Under Cab	6/3	9
DEF TANK 7 U.S. Gal. 26.5L Capacity, Frame Mounted Outside Left Rail, Under Cab	0/0	0
CAB Conventional	0/0	0
<u>Includes</u>		
: ARM REST (2) Molded Plastic; One Each Door		
: COAT HOOK, CAB Located on Rear Wall, Centered Above Rear Window		
: CUP HOLDERS Two Cup Holders, Located in Lower Center of Instrument Panel		
: DOME LIGHT, CAB Rectangular, Door Activated and Push On-Off at Light Lens, Timed Theater Dimming, Integral to Console, Center Mounted		
: GLASS, ALL WINDOWS Tinted		
: GRAB HANDLE, CAB INTERIOR (1) "A" Pillar Mounted, Passenger Side		
: GRAB HANDLE, CAB INTERIOR (2) Front of "B" Pillar Mounted, One Each Side		
: INTERIOR SHEET METAL Upper Door (Above Window Ledge) Painted Exterior Color		
: STEP (4) Two Steps Per Door		
HEATER SHUT-OFF VALVES (1) Ball Valve Type, Supply Line	5/0	5
GRAB HANDLE, CAB INTERIOR (2) Safety Yellow	0/0	0

<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
GAUGE CLUSTER English With English Electronic Speedometer	0/0	0
<u>Includes</u>		
: GAUGE CLUSTER (6) Engine Oil Pressure (Electronic), Water Temperature (Electronic), Fuel (Electronic), Tachometer (Electronic), Voltmeter, Washer Fluid Level		
: ODOMETER DISPLAY, Miles, Trip Miles, Engine Hours, Trip Hours, Fault Code Readout		
: WARNING SYSTEM Low Fuel, Low Oil Pressure, High Engine Coolant Temp, and Low Battery Voltage (Visual and Audible)		
GAUGE, OIL TEMP, AUTO TRANS , for Allison Transmission	1/0	1
GAUGE, AIR APPLICATION	1/0	1
GAUGE, AIR CLEANER RESTRICTION {Filter-Minder} With Black Bezel Mounted in Instrument Panel	2/0	2
IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster	0/0	0
GAUGE, DEF FLUID LEVEL	0/0	0
SEAT, DRIVER {National 2000} Air Suspension, High Back With Integral Headrest, Vinyl, Isolator, 1 Chamber Lumbar, With 2 Position Front Cushion Adjust, -3 to +14 Degree Angle Back Adjust	27/12	39
<u>Includes</u>		
: SEAT BELT 3-Point, Lap and Shoulder Belt Type		
MIRRORS (2) {Lang Mekra} Styled; Rectangular, Power Both Sides, Thermostatically Controlled Heated Heads, Clearance Lights LED, Bright Finish Heads & Brackets, Breakaway Type, 7.09" x 15.75" & Integral Convex Both Sides, 102" Inside Spacing	8/0	8
MIRROR, CONVEX, HOOD MOUNTED {Lang Mekra} Right and Left Side; 7.44" Sq., Bright	11/0	11
GRAB HANDLE Chrome; Towel Bar Type With Anti-Slip Rubber Inserts; for Cab Entry Mounted Left Side Only at "B" Pillar	3/0	3
SEAT, PASSENGER {National} Non Suspension, High Back, Fixed Back, Integral Headrest, Vinyl	15/8	23
SEAT BELT All Orange; 1 to 3	0/0	0
WINDSHIELD Heated, Single Piece	0/0	0
ARM REST, RIGHT, DRIVER SEAT	3/0	3
AIR CONDITIONER {Blend-Air} With Integral Heater & Defroster	42/5	47
<u>Includes</u>		
: HEATER HOSES Premium		
: HOSE CLAMPS, HEATER HOSE Mubea Constant Tension Clamps		
: REFRIGERANT Hydrofluorocarbon HFC-134A		
CAB SOUND INSULATION Includes Dash Insulator and Engine Cover Insulator	12/0	12
<u>Notes</u>		
: Feature included with CAB INTERIOR TRIM, Premium		
INSTRUMENT PANEL Center Section, Flat Panel	0/0	0
HVAC FRESH AIR FILTER	0/0	0
STORAGE POCKET, DOOR Molded Plastic, Full Width; Mounted on Passenger Door	0/0	0
CAB INTERIOR TRIM Deluxe	0/0	0
<u>Includes</u>		
: "A" PILLAR COVER Molded Plastic		

Description

: CAB INTERIOR TRIM PANELS Cloth Covered Molded Plastic, Full Height; All Exposed Interior Sheet Metal is Covered Except for the Following: with a Two-Man Passenger Seat or with a Full Bench Seat the Back Panel is Completely Void of Covering  
 : CONSOLE, OVERHEAD Molded Plastic; With Dual Storage Pockets with Retainer Nets and CB Radio Pocket  
 : DOOR TRIM PANELS Molded Plastic; Driver and Passenger Doors  
 : FLOOR COVERING Rubber, Black  
 : HEADLINER Soft Padded Cloth  
 : INSTRUMENT PANEL TRIM Molded Plastic with Black Center Section  
 : STORAGE POCKET, DOOR (1) Molded Plastic, Full-Length; Driver Door  
 : SUN VISOR (2) Padded Vinyl with Driver Side Toll Ticket Strap, Integral to Console

**F/R Wt** **Tot Wt**  
(lbs) (lbs)

CAB REAR SUSPENSION Air Bag Type	0/0	0
WINDSHIELD WIPER BLADES Snow Type	2/0	2
COWL TRAY LID	7/4	11
WHEEL, SPARE, DISC {Accuride 29300} 22.5x9.00 Rims, Powder Coat Steel, 10-Stud, 285.75mm BC, Hub-Piloted	0/0	0
WHEELS, FRONT {Accuride 29300} DISC; 22.5x9.00 Rims, Powder Coat Steel, 5-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs	0/0	0
WHEELS, REAR {Accuride 29169} DUAL DISC; 22.5x8.25 Rims, Powder Coat Steel, 5-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with .472" Thick Increased Capacity Disc and Steel Hubs	0/0	0
TIRE, SPARE Equal to Model Standard	45/46	91

Notes

: NOTE: Only One Spare Tire per Truck Ordered. Order Must Reflect Number of Tires Required (Including Spare). 10-Digit Tire Code and Spare Rim/Wheel Code Must be Specified.

WHEEL SEALS, REAR {Stemco Voyager} Oil Lubricated Wheel Bearings	0/0	0
WHEEL SEALS, FRONT {Stemco Voyager} Oil Lubricated Wheel Bearings ILO Standard Oil Seals	0/0	0
WHEEL BEARING, FRONT, LUBE {EmGard FE-75W-90} Synthetic Oil	0/0	0
(4) TIRE, REAR 12R22.5 G622 RSD (GOODYEAR) 482 rev/mile, load range H, 16 ply	0/72	72
(3) TIRE, FRONT 12R22.5 G661 HSA (GOODYEAR) 484 rev/mile, load range H, 16 ply	57/0	57

Cab schematic 100GN

Location 1: 2303, Red (Std)

Chassis schematic N/A

**Services Section:**

WARRANTY Standard for WorkStar 7300/7400 (4x2, 4x4, 6x4, 6x6), Effective with Vehicles Built January 2, 2015 or Later, CTS-2002U	0/0	0
--	-----	---

<b>Total Component Weight:</b>	<b>8402/4503</b>	<b>12905</b>
--------------------------------	------------------	--------------

The weight calculations included in this proposal are an estimate of future vehicle weight. The actual weight as manufactured may be different from the estimated weight. Navistar, Inc. shall not be liable for any consequences resulting from any differences between the estimated weight of a vehicle and the actual weight.



<u>Description</u>	<u>(US DOLLAR)</u>	<u>Price</u>
Factory List Prices:		
Product Items	\$121,590.00	
Service Items	\$0.00	
Total Factory List Price Including Options:		\$121,590.00
Freight	\$2,200.00	
Total Freight:		\$2,200.00
Total Factory List Price Including Freight:		\$123,790.00
Less Customer Allowance:		(\$41,155.00)
Total Vehicle Price:		\$82,635.00
Total Sale Price:		\$82,635.00
Total Per Vehicle Sales Price:		\$82,635.00
Total Net Sales Excluding Taxes:		\$82,635.00
Title And Municipal Plates	\$103.00	
Dealer DOC Fee	\$164.00	
Total License, Title, & Taxes:		\$267.00
Net Sales Price:		\$82,902.00

**Approved by Seller:**

**Accepted by Purchaser:**

\_\_\_\_\_  
**Official Title and Date**

\_\_\_\_\_  
**Firm or Business Name**

\_\_\_\_\_  
**Authorized Signature**

\_\_\_\_\_  
**Authorized Signature and Date**

RUSH TRK CTR OF N IL  
11816 S IL RTE 47  
HUNTLEY IL 60142  
847-669-5700

**This proposal is not binding upon the seller without  
Seller's Authorized Signature**

\_\_\_\_\_  
**Official Title and Date**

**The TOPS FET calculation is an estimate for reference purposes only. The seller or retailer is responsible for calculating  
and reporting/paying appropriate FET to the IRS.**