



Utility Tractors & Mowers - 031121
 CE and AG - 040319
 Utility Vehicles 122220
 NIPA Arkansas 4600041718
 NIPA Delaware GSS-17673
 Nebraska 14777 (OC)
 Mississippi 8200067336

KX080-4S2R3A WEB QUOTE #2796027

Date: 7/15/2024 12:49:21 PM

- Customer Information -

McLaughlin, Patrick
 58277

Village of Orland Park
 pmclaughlin@orlandpark.org
 7084036100

Quote Provided By
 Alta Equipment Company
 Chris May
 18405 115th Ave.
 Orland Park, IL 60467
 email: chris.may@altg.com
 phone: 8474170548

- Standard Features -

- Custom Options -



K Series

KX080-4S2R3A

*** EQUIPMENT IN STANDARD MACHINE ***

FEATURES

Eco Plus System
 Auto Idler
 Rubber Or Steel Track Models
 Air Conditioned ROPS/OPG
 (Top Guard, Level I) Cab
 Cloth Suspension Seat
 Kubota 2 Hydraulic Pump Load
 Sensing System
 2 Variable Displacement
 Pumps
 All Controls Hydraulic Pilot
 Controls
 Two Operating Pattern
 Selection System
 Accumulator
 Standard Front Dozer Blade w/
 Float
 Optional Float Angle Blade w/
 Bolt-on Cutting Edge
 360 Degree Full Rotation
 70 Degree Left, 60 Degree
 Right Boom Swing
 17.6 gpm Adjustable Auxiliary
 Hydraulics Port 1
 26.4 gpm Adjustable Auxiliary
 Hydraulics Port 2
 Thumb Bracket and Relief
 Valves
 Five Second Quick Preheat
 System
 Key Switch Stop System
 Half Pitch Rubber Tracks
 Self-Bleed Fuel System
 Auto-Downshift Two Speed
 Travel System
 Swivel Negative Brake
 Travel Negative Brake
 Third Line

ENGINE

V3307 Kubota DI CRS Turbo Tier 4
 Final Diesel Engine
 4 Cylinder, 4 Cycle
 62.3 Net HP @ 2200 rpm (SAE
 J1349)

OPERATIONAL

DIMENSIONS

Max Digging Depth 15' 1"
 Max Digging Radius @ Ground
 Level 23' 6.3"
 Max Vertical Digging Depth 12'
 7.6"
 Max Dumping Height 17' 2.7"

DOZER BLADE

DIMENSIONS

Width 86.6"
 Height 19.7"
 Lift Above Ground 19.7"
 Drop Below Ground 19.7"

PERFORMANCE

Digging Force @ Bucket (K7427)
 Digging Force @ Dipper Arm
 Travel Speed (Low / High)
 Climbing Ability
 Lift Capacity
 • Over Front
 • Blade Grounded
 • 4.0 Ft. Load Point Height
 • 12.0 Ft. Load Radius

**DIMENSIONS AND
 OPERATING WEIGHT**

KX080-4S2R3A, Rubber
 Tracks, Air Conditioned
 ROPS/OPG (Top Guard, Level
 I) Cab, Angle Dozer
 Blade, Dipper Arm, Counter
 weight,
 Overall Length 21' 1.9"
 Overall Width 7' 2.6"
 Overall Height 8' 4"
 Operating Weight* 18,280 lbs.
 Ground Clearance 15.4"

* Includes operator's weight,
 175 lbs.

KX080-4S2R3A Base Price: \$129,713.00

Configured Price: **\$129,713.00**

Sourcewell Discount: **(\$31,131.12)**

SUBTOTAL: **\$98,581.88**

Dealer Assembly: **\$0.00**

Freight Cost: **\$1,650.00**

PDI: **\$400.00**

Install of Wain Roy Swinger Attachment **\$550.00**

Total Unit Price: **\$101,181.88**

Quantity Ordered: **1**

Final Sales Price: **\$101,181.88**

Purchase Order Must Reflect Final Sales Price.

To order, place your Purchase Order directly with the quoting
 dealer

*Some series of products are sold out for 2022. All equipment specifications are as complete as possible as of the date on the quote. Additional attachments, options, or accessories may be added (or deleted) at the discounted price. All specifications and prices are subject to change. Taxes are not included. The PDI fees and freight for attachments and accessories quoted may have additional charges added by the delivering dealer. These charges will be billed separately. Prices for product quoted are good for 60 days from the date shown on the quote. All equipment as quoted is subject to availability.