

Box 1000, Winn, Michigan, 48896

Telephone: 989-866-2381 Fax: 989-866-2280 www.morbark.com



Sold To:	14700 Rabinia	nge of Orland Park 00 Rabinia Ave and Park, IL 60462			Alexander Ed 4728 Yender Lisle, IL 6053 Attn: Matt Lin		
Quote No.	2131TA-0106	Quote Date: 1/6/2021	_ Customer P.O.	Sourcewell ID#58277  708-403-6108  mmazza@orlandpark.org		Requested:	120-150 Days ARO
	Contact:	Mike Mazza	_ Contact #:				Delivery Instructions: FOB-Destination
	Preparer:	Erika Snyder	Terms:	Net 30 Day			. 02 200

# SKU# 50121 - 2021 MORBARK EEGER BEEVER™ 2131-TA (formerly known as M18R-TA)

#### **EQUIPMENT AND OPTIONS**

#### STANDARD UNIT:

- Morbark orange urethane paint system
- Infeed with rigid tray and control handle to actuate feed wheels and dual safety pull cables
- Dual horizontal feed wheels with TorqMax<sup>™</sup> top feed wheel compression system, hydraulic lift assist, Variable Force<sup>™</sup> constant hydraulic down pressure system with additional manually applied hydraulic down pressure at the valve handle and direct drive bottom feed wheel with box mount coupler
- · Reversing automatic feed system
- 37-3/8" diameter x 23-3/4" wide, four (4) dual-edged knife staggered pocket drum with removable knife holders, dual sided chambered air impeller system and controllable air flow vents
- 60-gallon lockable fuel tank with drain plug, sight gauge, shut-off valve and electronic fuel gauge
- 41-gallon lockable hydraulic reservoir with sight gauge, drain plug, hydraulic oil cooler and clean-out cover
- Live hydraulic system including: ball valve, pump, motor, and valve bank with additional valve section for installation of winch package
- Hydraulic swivel discharge with 360° rotation, turnbuckle height adjustment, bottom clean-out door and adjustable flipper
- 6" x 2" tubular steel frame with cross bracing for additional structural rigidity
- 6" x 4" tubular steel telescoping drawbar with (2) 12" extensions, adjustable hitch plate with 2-1/2" pintle ring and 3/8" thick safety chains with clasp hooks
- 16,000# Torsion tandem axles, electric brakes, break-away actuator with 235/75R x 17.5", 16-ply radial tires and hexagon splash guard fenders
- Hydraulic front stabilizer
- Lockable steel combination tool and battery box compartment with 8D, 1400CCA battery
- Registration and operator guide holder
- Complete set of manuals including: Safety and Operator's, Parts Manual with electronic back-up, which also
  includes a Safety Video and OEM component manuals. Also included is an engine manual if applicable along
  with start-up paperwork
- Enclosed engine with gauge panel, radiator fines screen and slide rails for belt adjustment
- Trailer wiring package includes: 7-pin flat electrical connector, LED tail lamps, LED side marker lamps, tail lights, and license plate holder with light

### **POWER OPTIONS:**

• John Deere 4045HFC06, 173-HP, Tier 4F diesel engine with over center clutch and block heater in lieu of standard

## OPTIONS:

- Variable speed flow control
- Winch package: Heavy-duty, 5000# pull capacity with rope, 10' chafe guard and interlock device

### 

**QUOTE IS VALID FOR 30 DAYS**